Hadoop Security Design?

Just Add Kerberos? Really?

Andrew Becherer
Black Hat USA 2010



Agenda

- Conclusion
- What is Hadoop
- Old School Hadoop Risks
- The New Approach to Security
- Concerns
- Alternative Strategies
- A Security Consultant Walks Into a Datacenter



Conclusion

Did Hadoop Get Safer?

Conclusion

Hadoop made significant advances but faces several significant challenges



What is Hadoop


MapReduce Simplified View Who Is Using It

MapReduce

- Name Nodes & Data Nodes
 - Data Access
- Job Tracker
 - Job Submission
- Task Tracker
 - Work
- Optional other services
 - Workflow managers
 - Bulk data distribution



Simplified View





Who is Using It







Booz | Allen | Hamilton











News Corporation





The New York Times



Hadoop Risks

Insufficient Authentication
No Privacy & No Integrity
Arbitrary Code Execution
Exploit Scenario

Insufficient Authentication

- Hadoop did not authenticate users
- Hadoop did not authenticate services



No Privacy & No Integrity

- Hadoop used insecure network transports
- Hadoop did not provide message level security



Arbitrary Code Execution

 Malicious users could submit jobs which would execute with the permissions of the Task Tracker



Exploit Scenario

- Alice had access the Hadoop cluster
- Bob had access the Hadoop cluster
- Alice and Bob had to trust each other completely
- If Mallory got access to the cluster Alice and Bob both died in a fire.



The New Approach

Kerberos

Delegation Tokens

New Workflow Manager

Stated Limitations

Kerberos

- Users authenticate to the edge of the cluster with Kerberos (via GSSAPI)
- Users and group access is maintained in cluster specific access control lists



Delegation Tokens

- To prevent bottlenecks at the KDC Hadoop uses various tokens internally.
 - Delegation Token
 - Job Token
 - Block Access Token
- SASL with a RPC Digest mechanism



New Workflow Manager

- Oozie
- Users authenticate using some "pluggable" authentication mechanism
- Oozie is a superuser and able to communicate with Job Trackers and Name Nodes on behalf of the user.



Stated Limitations

- Users cannot have administrator access to nodes in the cluster
- HDFS will not transmit data over an untrusted networks
- MapReduce will not transmit data over an untrusted networks
- Security changes will not impact GridMix performance by more than 3%.



Concerns

Quality of Protection (QoP)

Massive Scale Symmetric Cryptography

Pluggable Web UI Authentication

IP Based Authentication

Quality of Protection (QoP)

Authentication Integrity Privacy



Symmetric Cryptography

- Block Access Tokens are used to access data
- TokenAuthenticator = HMAC-SHA1(key, TokenID)
- The secret key must be shared between the Name Nodes and all of the Data Nodes
 - SHARED WITH ALL OF THE DATA NODES!!! That is a lot of nodes.



Pluggable Web UI Authentication

- There are multiple web Uis
 - Oozie
 - Job Tracker
 - Task Tracker
- With no standard HTTP authentication mechanism I hope your developers are up to it.



IP Based Authentication

- HDFS proxies use the HSFTP protocol for bulk data transfers
- HDFS proxies are authenticated by IP address



Alternative Strategies

Tahoe

Tahoe - A Least Authority File System

- Deserves its own talk
 - Aaron Cordova gave one at Hadoop World NYC 2009
- Disk is not trusted
- Network is not trusted
- Memory is trusted
- Intended for use in Infrastructure as a Service cloud computing environments
- Write performance is terrible but read performance is not so bad



Assessing Hadoop

Targets

Tokens

Targets

- Oozie is a superuser capable of performing any operation as any user
- Name Nodes or Data Nodes can give access to all of the data stored in HDFS by obtaining the shared "secret key"
- Data may be transmitted over insecure transports including HSFTP, FTP and HTTP
- Stealing the IP of an HDFS Proxy could allow one to extract large amounts of data quickly



Tokens: Gotta Catch 'em All

- Kerberos Ticket Granting Token
- Delegation Token
 - Get the Shared Key if Possible
- Job Token
 - Get the Shared Key if Possible
- Block Access Token
 - Get the Shared Key if Possible



Thank you for coming! andrew@isecpartners.com

